

# MDC ACOUSTIC SOLUTIONS

FEATURING **zintrac<sup>®</sup>**

847-437-4000 | [mdc.is/zintrac](https://mdc.is/zintrac)



Zintrac 1/8" Acoustic Panels Charcoal

## 1/8" ACOUSTIC PANELS

Technical Specifications

AUGUST 2024



Zintra 1/8" Acoustic Panels wrapped panels in Cloud

Zintra 1/8" Acoustic Panels sheets are perfect for use as wrapped panels, on curved surfaces or as a seamless wallcovering for commercial, hospitality and institutional projects.

**MDC** ACOUSTIC SOLUTIONS  
FEATURING **zintra**





Zintra 1/8" Acoustic Panels wrapped panels in Dove



Zintra 1/8" Acoustic Panels Snow installed onto curved surface

STANDARD  
COLORS


Pewter

Slate

Smoke

Tar

Frost



Pewter

Slate

Smoke

Tar

Frost

Zintra 1" Acoustic Panels color range

## DIMENSIONS

Nominal 4' x 9' x 1/8" (exact size 48.25" x 110" x 1/8")  
 Thickness tolerance +/- .02"  
 Width and length tolerance +/- 1/8"

## MATERIAL COMPOSITION

100% Solution Dyed Polyester

## WEIGHT

0.12 lb / ft<sup>2</sup>

## FIRE RATING

ASTM-E84 — Class A classification  
 AS ISO 9705 — 2003 — Group 1 classification  
 EN-13501 — B-s2-d0 Classification

## TEMPERATURE

The maximum temperature exposure is 240° F (115° C)

## LIGHTFASTNESS

AATCC 16.3, Option 3: Panel color change at 40AFU is 4.5

## MOISTURE ABSORPTION

Polyester fiber when exposed to an atmosphere of 120°F (49° C) at 90% relative humidity for four days showed moisture absorption of less than 0.03% by weight.

## VOC TESTING

In accordance with Standard Method Version 1.2 for CDPH 01350, Zintra Acoustic Panels received a PASS for all testing scenarios.

## APPLICATION

Indoor areas only.

## SURFACE FINISH

Zintra Acoustic Panels have a matte surface on both side "A" and side "B" and are suitable to use as the face surface. When installing panels side-by-side, it is recommended that the face surfaces are installed as either all "A" or all "B" to ensure consistency of finished look.

## FABRICATION

Utility knife and CNC with oscillating knife.

## INSTALLATION

As a wallcovering: Dry hang with adhesive using an overlap and double cut method.

Wrapping Panels: To wrap panels, staple off to the back

Visit [mdc.is/Zintra](https://mdc.is/Zintra) to download available Installation Guides for more details.

## SUSTAINABILITY

Certified by Declare, GREENGUARD and HPD, Zintra is made from 100% recyclable materials:

- 60% post-consumer recycled content from PET bottles.
- 35% pre-consumer recycled content from PET chips
- 5% polylactic acid (PLA)

Zintra also has low levels of volatile organic compounds, contain no formaldehyde, meets the Global Recycled Standard and is Red List Free.

## CARE INSTRUCTIONS

Vacuum to remove dust.

Remove spills immediately. Dab Zintra with a damp clean cloth and mild solution of liquid detergent and warm water. Repeat only using clean water, then pat dry with a lint free cloth.

For difficult stains and to disinfect, bleach can be used in accordance with CDC Cleaning and Disinfection instructions. The solution ratio should be 5 tablespoons of bleach to 1 Gallon (3.7 ltr) of water or 4 teaspoons of bleach per quart (0.95 ltr) of water. Spray apply the solution as a mist and then wipe off the surface moisture. To remove the bleach, repeat using a clean, water dampened cloth, then pat dry.

Polyester carpet and fabric cleaners can be used.

With all cleaning applications - ***always test an inconspicuous area first.***

A stain repellent coating is available for additional protection.

## MDC ADVANTAGE

- Top acoustical installers prefer our product and our customer service team.
- 9 years of experience working through challenges to become experts.
- Fabrication capabilities for all design solutions.
- National team of Account Executives to support projects in any location.



HOW TO SPECIFY

Ideal for walls, ceilings, screens, partitions, millwork and more, Zintra is easily fabricated and installed to offer the simplest acoustic solution. While specifying Zintra Acoustic Panels for your space, consider the following:

PANEL SIZE:

- Standard Panel: 4'x9' (nominal (48.25"x110"), true (48"x108") or custom)

PANEL THICKNESS:

- Standard Panel: 1/8"

COLOR:

- Select Panel color from available color list

QUANTITY:

- Number of panels required or dimensions of space

INSTALLATION:

- Installation method: direct adhere
- visit [mdc.is/zintra](https://mdc.is/zintra) for detailed installation instructions

Questions? MDC is here to help!

At MDC, we believe the very best design partnerships are created from a shared vision paired with keen expertise. Our goal is to always celebrate and support your unique design perspective, which is why we strive to create products abundant in aesthetic appeal and approachable functionality. Together, let's navigate your next project from the initial inspiration to a finished product. Together, let's make it happen.

For more information visit:

**MDC.IS/ZINTR**

MDC INTERIOR SOLUTIONS  
400 HIGH GROVE BOULEVARD  
GLENDALE HEIGHTS, IL 60139

ZINTR@MDCWALL.COM  
847.437.4000

 | MDCWALL.COM

