

Door Skins

Product Specification

PRODUCT FEATURES

Sheet Size 48" Wide x 84" Long

Construction .013 PVC film

Stock Collection Always available when you need it.

High Impact Finish Quality durability for high-traffic areas.

Easy Adhesion & Fabrication Application made simple.

Chemical Resistant Cleaning and disinfectant resistant.

Class A Fire Rated With 3M Fire Rated Adhesive on Fire Rated Door.

Cut to Fit Common Door Sizes Standard door sizes that meet most specs.



PERFORMANCE SPECIFICATIONS

| Property | Test Method | Typical Value |
|------------------------|--|--|
| Light Fastness | DIN EN ISO 4892-2, 2006-06 DIN EN ISO 105 B 02, 2002-07 | > 6 (blue scale) |
| Chemical Resistance | DIN EN 12720, 1997-10 | Class 1 B (*1) |
| Scratch Resistance | DIN 68861/4, 1981-12 | Class 4 D (> 1,0-1,5 N) |
| Resistance to Dry Heat | DIN 68861/7, 2001-04 | Class 7 C (100°C) |
| Abrasion Resistance | DIN 68861/2, 1981-12 | Class 2 B (>350-650 rpm) |
| Tensile Strength | DIN EN ISO 527-3/2/200, 2003-07 | Longitudinal > 40 N/mm2 Transverse > 30 N/mm2 (depending on embossing) |

FINISHES



Noce Secchia




Driftwood



Concrete Groovz

Medium Cherry





Medium Walnut




Weathered Oak



Dark Walnut



Artic Groovz



Gloss White



Portuna