

General Information

Dimension Ceiling Tiles are formed thermoplastic tiles with stain and impact resistance. The panels are available in over 40 textures for 2' x 2' lay in applications. There are matte and gloss options in 45 different finishes. They can be used as a decorative product where other acoustical 2' x 2' lay in tiles are typically used.

Specifications

2' x 2' x .030". This is a dimensional product, so actual thickness varies by pattern

PROPERTY	TEST METHOD	TYPICAL VALUE
Fire Retardant	ASTM E-84	Class A
QUV		Minimum 1,500 hours
Solvent Resistance		50 MEK
Humidity		12 hrs 96-100% RH @ 40 degrees C on MDF
MEK Double Rubs		Withstands 70 cycles
Impact Resistance	ASTM D5420	>2 inch lbs per mill of thickness

STAIN RESISTANCE		
	24 Hrs	7 Day
Wesson® Oil	N	N
Household Ammonia	N	N
409® all purpose cleaner	N	N
Tide® laundry detergent	N	N
Isopropyl Alcohol	N	N
Clorox®	N	N
Grape Juice	N	N
Orange Juice Concentrate	N	N
Coffee	N	N
Mustard	N	N
Ketchup	N	N
Red wine	N	N
Coca-Cola®	N	N
Water	N	N
Black crayon	N	N
Lipstick	N	N
Pine-Sol®	N	N
Vinegar	N	N

N = no change

S = slight change

M = medium change

L = large change