

# FUZE

DRY ERASE PAINT

## Product Specifications

<b>Kit Contents:</b>	Large Container Part A & Small Container Part B ¼ Inch Nap Roller & 1 Stir Stick
<b>Coverage:</b>	Kits cover approximately 100 or 400 square feet of surface area
<b>Characteristics:</b>	Available in white, clear, custom colors and metallics Clear can be painted over any eggshell sheen latex based paint – regardless of color Longest pot life in the industry – 4 hours – Lower cost of installation Can be applied by roller or spray applied Isocyanate Free Low Volatile Organic Compound (VOC) content of less than 100 grams per liter as mixed Part A – less than 3 g/l and Part B – 0 g/l Highly chemical and stain resistant LEED NC 2009 Compliant
<b>Application:</b>	Apply with the supplied roller over smooth, non-porous painted surfaces including drywall, marker board, chalkboard, metal, and glass, as well as smooth vinyl wallcovering. Opening, mixing, and installing FUZE should be done by a professional installer, in accordance with the <i>Application Instructions</i> .
<b>Preparation:</b>	Surface should be dry, prepared to Level 4 or 5 smoothness, and free of grease, mildew, dust and any imperfections. Spray application of primers/sealers and base color coat of paint is preferred. Scuff sanding is recommended for high gloss surfaces.
<b>Pot/Shelf Life:</b>	4 hour open time / 36 month shelf life, providing product is not opened and is properly stored
<b>Cure Time:</b>	Ready for use after 5 days, although 7 days will allow for varying climates.
<b>Environmental:</b>	Free of formaldehyde, harmful carcinogens, chromium, lead, and mercury Low VOC content of <90 g/L meets Green Seal standards for paints and coatings Qualifies for contribution to LEED Credit 4.2—Low-Emitting Materials Meets or exceeds environmental criteria for non-flat coatings according to the U.S. Environmental Protection Agency, U.S. Green Building Council, Canada Green Building Council, South Coast Air Quality Management District, and the California Air Resources Board
<b>Markers:</b>	For best performance, use MDC or Expo Regular dry erase markers.
<b>Maintenance:</b>	For daily erasing and cleaning use a clean, dry-erase cotton cloth, or microfiber towel. Periodically use a clean damp cloth, dry-erase cleaner, or wipes to maintain surface.
<b>Warranty:</b>	10-year limited warranty from date of shipment

For more helpful tips, please go to [www.mdcwall.com/FUZE](http://www.mdcwall.com/FUZE).