

SAFETY DATA SHEET

Product Name: MDC FUZE DRY ERASE Paint with IsoFree™ Technology [Marker Board Paint] Part B

Product Codes: FUZE60C, FUZE60W, FUZE 250C, FUZE250W

SECTION 1: Identification

MANUFACTURER: Rainguard Brands, LLC
RainguardPro
2736 West McDowell Road
Phoenix, AZ 85009
United States of America

RAINGUARD PHONE: (949) 515-8800

POISON CENTER: (800) 222-1222

EMAIL: support@rainguardpro.com

WEBSITE: rainguardpro.com

REVISION DATE: 01/31/2025

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 4	Combustible liquid
Acute toxicity (inhalation:dust,mist) Category 4	Harmful if inhaled
Skin corrosion/irritation Category 2	Causes skin irritation
Serious eye damage/eye irritation Category 2	Causes serious eye irritation
Respiratory sensitization, Category 1	May cause allergy or asthma symptoms or

Skin sensitization, Category 1

breathing difficulties if inhaled.

May cause an allergic skin reaction

Specific target organ toxicity – Single exposure, Category 3,

May cause respiratory irritation

Respiratory tract irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS label elements :



Signal Words:

Danger

Hazard statements (GHS US)

Combustible liquid

Causes skin irritation

May cause an allergic skin reaction

Causes serious eye irritation

Harmful if inhaled

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause respiratory irritation

PRECAUTIONARY STATEMENTS (GHS US)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Avoid breathing mist, spray, vapors, gas.

Wash hands, forearms and face thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of inadequate ventilation] wear respiratory protection.

If on skin: Wash with plenty of water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a poison center or doctor.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use media other than water to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

3.08% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

29.93% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

SECTION 3: Composition

3.1. Substances

Full text of hazard classes and H-statements : see section 16

SECTION 4: First Aid Measures

4.1. Description of first aid measures

First-aid measures general	: First aider: Pay attention to self-protection. Never give anything by mouth to an unconscious person. Give artificial respiration if necessary. Induce artificial respiration with mask fitted with one-way valve or other suitable device but not mouth-to-mouth. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim is unconscious : Lay in a stable manner on victim's side. Induce artificial respiration with mask fitted with one-way valve or other suitable device; not mouth-to-mouth. Call a physician immediately.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do NOT induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: Stinging, redness, itching, tears, blurred vision, swelling.

Symptoms/effects after ingestion : Ingestion may cause nausea and vomiting.

Most Important Symptoms/Effects : Irritation to eyes, skin and respiratory tract. May cause an allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire Fighting Measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry chemical, CO₂, or water spray or regular foam.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid.

Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. Use extinguishing media appropriate for surrounding fire. Move containers from fire area if it can be done without personal risk. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid all personal contact including breathing in the mist,

spray, vapors, gas. Do not take actions involving personal risks. Absorb spillage to prevent material-damage. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Evacuate the danger area. If outdoors, move to an area upwind of the danger area. If possible without taking personal risks, remove ignition sources, ventilate area. Avoid breathing mist, spray, vapors, gas. Avoid contact with skin and eyes. No open flames, no sparks, and no smoking. Prevent other non-emergency personnel from entering the danger area.

6.1.2. For emergency responders

Protective equipment : Wear the recommended personal protective equipment.

Emergency procedures : Evacuate personnel to a safe area. Ventilate spillage area. Stop leak if safe to do so.

6.2. Environmental precautions

Do not let the product reach soil, drains, sewers, or surface and ground water.

6.3. Methods and material for containment and cleaning up

For containment : Contain with non-combustible inert absorbent.

Methods for cleaning up : Take up in non-combustible inert absorbent and place into container for disposal. Contaminated absorbent material may pose the same hazard as the spill product. Decontaminate surfaces and equipment with water and detergent. Until a sufficient level of dilution is achieved, the decontamination water may pose the same hazards as the product. Notify authorities if product enters sewers or public waters. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Wear personal protective equipment. Avoid breathing mist, spray, vapors, gas. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a cool, dry and well-ventilated area away from incompatible substances. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store tightly closed until ready for use.

Incompatible products : Oxidizing agents.

Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure Controls and Personal Protection

8.1. Control parameters

RainguardPro® MuralGuard® (PartB)

No additional information available

USA - ACGIH - Occupational Exposure Limits

Local name	Hexamethylene diisocyanate
ACGIH OEL TWA	0.005 ppm (IFV - Inhalable fraction and vapor)
Remark (ACGIH)	TLV® Basis: URT irr; resp sens. Notations: BEI
Regulatory reference	ACGIH 2024

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Use general ventilation, local exhaust ventilation or process enclosure to keep

the airborne concentrations below the permissible exposure limits. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Environmental exposure controls : Avoid release to the environment. Take measures to reduce or limit air emissions and releases to soil and the aquatic environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Personal protective equipment should be chosen according to national standards and in discussion with the supplier of the protective equipment. Wear recommended personal protective equipment.

Hand protection:

Wear protective gloves. The following materials are suitable for protective gloves: Neoprene or nitrile rubber gloves, Butyl rubber

Eye protection:

Safety glasses with side guards should be worn to prevent injury from airborne particles and/or other eye contact with this product

Skin and body protection:

Body protection should be chosen depending on activity and possible exposure. Wear suitable protective clothing

Respiratory protection:

Use NIOSH approved respirator if ventilation is inadequate. SCBA for emergency responders. Must be used in accordance with an OSHA complaint respiratory protection program.

Personal protective equipment symbol(s):



SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid.
Appearance	: Liquid.

Color	: Colorless
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and Reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Inhalation:dust,mist: Harmful if inhaled.

RainguardPro® MuralGuard (PartB)

ATE US (dust, mist)	3.801 mg/l/4h
Unknown acute toxicity (GHS US)	3.08% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 29.93% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

Aliphatic polyisocyanate

LD50 oral rat	> 2500 mg/kg body weight
LD50 dermal rat	> 2000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg body weight
LC50 Inhalation - Rat	3.9 mg/l/4h

Ethyl-diisopropylamine

LD50 oral rat	200 – 2000 mg/kg body weight
LD50 dermal rat	> 2000 mg/kg body weight
LC50 Inhalation - Rat	2.63 mg/l/4h

Hexamethylene-di-isocyanate

LD50 oral rat	746 mg/kg
LD50 dermal rat	> 7000 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.

Aliphatic polyisocyanate

Skin corrosion/irritation, rabbit	Moderately irritating
-----------------------------------	-----------------------

Ethyl-diisopropylamine

Skin corrosion/irritation, rabbit	Moderately irritating
Serious eye damage/irritation	: Causes serious eye irritation.

Aliphatic polyisocyanate

Skin sensitization, Guinea pig	(Positive)
--------------------------------	------------

Ethyl-diisopropylamine

Additional information	No sensitizing reaction was observed for guinea pigs
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Reproductive toxicity : Not classified
STOT-single exposure : May cause respiratory irritation.

Aliphatic polyisocyanate

STOT-single exposure : May cause respiratory irritation.

Hexamethylene-di-isocyanate

STOT-single exposure : May cause respiratory irritation.
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available
Symptoms/effects after inhalation : Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact : May cause an allergic skin reaction. Irritation (itching, redness, blistering).
Symptoms/effects after eye contact : Stinging, redness, itching, tears, blurred vision, swelling.
Symptoms/effects after ingestion : Ingestion may cause nausea and vomiting.
Most Important Symptoms/Effects : Irritation to eyes, skin and respiratory tract. May cause an allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

SECTION 12: Ecological Information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Aliphatic polyisocyanate

EC50 72h - Algae [1] : > 1000 mg/l

Ethyldiisopropylamine

LC50 - Fish [1]	69.7 mg/l
EC50 - Crustacea [1]	28.1 mg/l
EC50 72h - Algae [1]	196 mg/l
NOEC chronic fish	14 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal Considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations. Dispose of this material and its container at hazardous or special waste collection point. Refer to all applicable national, international and local regulations or provisions.
Additional information	: Do not re-use empty containers.
Ecological information	: Avoid release to the environment.

SECTION 14: Transportation Information

In accordance with DOT / IMDG / IATA

14.1. UN number

DOT NA No : NA1993
UN-No. (IMDG) : Not regulated
UN-No. (IATA) : Not regulated

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Combustible liquid, n.o.s. (Dipropylene Glycol Dimethyl Ether)
Proper Shipping Name (IMDG) : Not regulated
Proper Shipping Name (IATA) : Not regulated

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Combustible liquid

IMDG

Transport hazard class(es) (IMDG) : Not regulated

IATA

Transport hazard class(es) (IATA) : Not regulated

14.4. Packing group

Packing group (DOT) : III
Packing group (IMDG) : Not regulated
Packing group (IATA) : Not regulated

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT)	: NA1993
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on passenger vessel.

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory Information**15.1. US Federal regulations**

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Hexamethylene-di-isocyanate (822-06-0)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ

100 lb

15.2. International regulations

CANADA

EU-Regulations

No additional information available

National regulations

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other Information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H227	Combustible liquid
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.