

### PRODUCT FEATURES

#### Sheet Size

3000 x 2100 mm

#### Stock Collection

3000 x 2100 mm

#### High Impact Finish

3000 x 2100 mm

#### Easy Adhesion & Fabrication

3000 x 2100 mm

#### Chemical Resistant

3000 x 2100 mm

#### Class A Fire Rated

3000 x 2100 mm

#### Cut to Fit Common Door Sizes

3000 x 2100 mm



### PERFORMANCE SPECIFICATIONS


Property	Test Method	Typical Value
Light Fastness	DIN EN ISO 4892-2, 2006-06 DIN EN ISO 105 B 02, 2002-07	> 6 (blue scale)
Chemical Resistance	DIN EN 12720, 1997-10	Class 1 B (*1)
Scratch Resistance	DIN 68861/4, 1981-12	Class 4 D (> 1,0-1,5 N)
Resistance to Dry Heat	DIN 68861/7, 2001-04	Class 7 C (100°C)
Abrasion Resistance	DIN 68861/2, 1981-12	Class 2 B (>350-650 rpm)
Tensile Strength	DIN EN ISO 527-3/2/200, 2003-07	Longitudinal > 40 N/mm <sup>2</sup> Transverse > 30 N/mm <sup>2</sup> (depending on embossing)

Color: RAL 9005


BMTPBWB, BCMF, (MPTT8, F




Noce Secchia



Concrete (SPPW)




Finesse



Weathered Oak



Artic Groovz



Dark Walnut

Driftwood

Medium Cherry

Medium Walnut

Portuna