MDC PrimeSeal

Latex Emulsion/Pigment Dispersion Primer

MCT20060824

MDC Wallcoverings 400 High Grove Blvd Glendale Heights, IL 60139 800-621-4006 www.MDCWallFinishes.com Medical & Transport Emergency: INFOTRAC **800-535-5053**

MSDS Date: 11-13-2013 Supersedes: All Previous

Product Identification

Trade Name: **MDC PrimeSeal™ Primer**Chemical Family: Latex Emulsion/Pigment Dispersion

DOT Classification: Not Regulated
CAS Number: Mixture

Application

Thickness Wet: 3.5 mils

Coverage: 450 sq. ft.

Thickness Dry: 1.0 mils

Application: Brush, Roll or Spray

Physical Data

Boiling Range (F): 212 (water)

Freezing Point (F): 32 (water)

Vapor Density (Air=1): >1

Solubility in Water: Dilutable Specific Gravity: 1.2

Ph Information: 9.0-10.0

Vapor Pressure (mmH@68f): 17 Appearance & Odor: Liquid, white color, latex

Evaporation Rate: (Butyl Acetate=1): <1 (water) smell

Hazardous Ingredients

Ingredient	Percent	PPM	MG/M3	CAS Number
None				

This paint mixture contains titanium dioxide and/or other pigments classified by ACGIH as "nuisance dusts." Exposures to spray mist or sanding dust should be controlled to below 10mg/m3 through usage of NIOSH/ MSHA TC23C or equivalent approved dust filter respirators. Follow respirator manufacturer's directions for use.

SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CRF 372:

NONE above de minimis concentrations.

HMIS RATING: Health=1 Flamability=0 Reactivity=0

*User should determine appropriate personal protective equipment based on use conditions.

	Fire & Explosion Hazard Data	Fire Extinguishing Media
F	Flash Point: Not determined (aqueous system)	Non-flammable (aqueous emulsion)
l	LEL: Not determined (aqueous system)	If water evaporates, remaining materiel can burn.
ļι	JEL: Not determined (aqueous system)	Use all-purpose foam for large fires, and CO2 or
		dry chemical media for small fires.

Special Fire Fighting Procedures: Use self-contained breathing apparatus when fighting enclosed fires.

Unusual Fire and Explosion Hazards: Products will not burn but may spatter if temperature exceeds boiling point of water. Dried solids can burn, giving off oxides and carbon.

Reactivity Data

This product is stable under normal (Ambient) conditions and hazardous polymerization will not occur.

Hazardous Decomposition Products: Combustion of dried film may produce Carbon Dioxide and Carbon Monoxide.

Conditions or materials to Avoid: None.

MDC PrimeSeal

Latex Emulsion/Pigment Dispersion Primer

MCT20060824

Health Hazard Data

Effects of Acute Over Exposure:

Inhalation: Trace component, residual monomer, and other organics may be irritating to eyes, skin, mucous membranes, respiratory tract and may produce symptoms of headache and nausea in poorly ventilated areas.

Ingestion: Irritating to gastrointestinal tract, abdominal pain, and diarrhea.

Skin Contact: Prolonged contact can cause transient reddening of the skin.

Eye contact: Direct contact may be irritating to eyes.

Effects of Repeated Overexposure: This mixture as provided shows no evidence of chronic effects from available information.

EMERGENCY FIRST AID PROCEDURES

Eye contact: Immediately flush eyes for 15 minutes occasionally lifting eyelids. If victim wears contact lenses, remove lenses and continue rinsing. If irritation continues, consult a physician.

Skin contact: Wash effected area thoroughly with mild soap and water. If irritation develops and persists, consult a physician.

Inhalation: Move to fresh air if necessary. If irritation persists, consult a physician. If victim is not breathing, artificial respiration should be administered by qualified personnel. Seek immediate medical attention.

Ingestion: If swallowed, dilute with water and consult a physician.

Toxicity Data

Note: Formaldehyde may be generated under acid conditions. Maintain adequate ventilation under these conditions to prevent exposure above TWA 0.3 ppm and STEL of 0.6 ppm.

Spill or Leak Procedures

Spills: Major spills should be collected for disposal. Minor spills may be flushed to sewer if permitted by local, state, and federal regulations.

Waste Disposal: Incinerate or bury in suitable landfills where permitted by appropriate government regulations.

Special Protection Information

Respiratory Protection: Use appropriate MAHA/NIOSH approved respirator in areas with poor ventilation and when exposed to spray mists or sanding dusts.

Ventilation: General room ventilation is expected to be satisfactory. Use local exhaust if needed for mist or vapor.

Protective Gloves: Wear gloves impervious to water and soap.

Eye Protection: Wear goggles if spraying and available eye bath.

MDC PrimeSeal

Latex Emulsion/Pigment Dispersion Primer

MCT20060824

Disclaimer

The information in this MSDS was obtained from sources we believe are reliable. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness.

The conditions of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.

Disposal of containers should be in accordance with applicable federal, state and local laws and regulations.